

LEVERAGING TECHNOLOGIES TO REDUCE INJURIES



MODEL SHOWN
3601490

- **PIVOTING ANCHOR AND CARABINER**
Centers the load and is large for an easy connection
- **ALUMINUM HOUSING**
Provides exceptional strength, durability and corrosion resistance
- **SEALED DESIGN**
Ensures efficient, safe operation under the harshest working conditions
- **CARRYING HANDLE**
Built-in design for easy transport, and can be used for dropped objects protection
- **STAINLESS STEEL CABLE**
Resists abrasion and corrosion
- **2.4 M (8 FT.) TAIL WITH CLEAR TUBE**
Protects cable in the work environment and allows for easy inspection
- **ERGONOMIC CABLE HANDLE**
Provides added comfort and ease-of-use when making connections
- **STAINLESS STEEL TRIPLE LOCKING SWIVEL HOOK WITH 16 kN (3600 LB.) GATE**
Limits lifeline twisting

Equipped with



LIMIT FORCES. WARN OPERATOR. REDUCE INJURY.

LEVERAGING SEALED-BLOK™ TECHNOLOGY

The Sealed Tension Limiter™ connects in line between the suspended worker and the winch line. If the worker becomes entangled, the deployment of a bright yellow cable cues the crane operator to stop. When the Sealed Tension Limiter™ deploys, it limits loads to reduce the possibility of severe injury. Following the activation, the device automatically resets.



DURABLE

Heavy-duty design stands up to the harshest environments.

- Corrosion resistant
- Stainless steel end-plates
- Aluminum housing

RELIABLE

Dynamic components sealed inside the housing to protect against moisture/water penetration and the finest particulate contaminants.

TRUSTED

The Sealed Tension Limiter™ design is based upon proven DBI-SALA® Sealed-Blok™ technology to ensure the Sealed Tension Limiter™ will perform in any environment and endure virtually any condition.

SPECIFICATIONS:

- **Model:** 3601490
- **Rated Capacity:** 59-141 kg (130-310 lbs.) - Single user only
- **Total Deployment:** 7 m (23 ft.)
- **Weight:** 9.7 kg (21.3 lbs.)
- **General Construction:** Aluminum and stainless steel components
- **Lifeline Material:** Stainless steel
- **Carabiner:** Stainless Steel, 16 kN (3,600 lb.) triple action
- **Deployment Force:** 181-408 kg (400-900 lbs.)

PLEASE NOTE: THIS PRODUCT ALONE WILL NOT MAKE A MATERIAL WINCH A MAN-RATED WINCH.

The Sealed Tension Limiter™ is designed to limit the loading force a person could be subjected to should they become entangled in the structure while the main winch line continues to operate. ALWAYS use a separate fall protection device with the Sealed Tension Limiter™ device.

Capital Safety Group, EMEA
5a Merse Road, North Moons Moat,
Redditch, Worcestershire B98 9HL
t: +44 (0) 1527 548 000 | f: +44 (0) 1527 591 000
Le Broc Center, Z.I. 1re Avenue, BP 15,
06511 Carros Le Broc Cedex
t: +33 (0)4 97 10 00 10 | f: +33 (0)4 93 08 79 70
www.capitalsafety.com information@capitalsafety.com

