



SRG-UNI-1,5



SRG-1,5

Manhole and Cone Chain Clamp SRG

For transporting manhole rings and cones.

SRG-1,5, SRG-3 and SRG-3-L suitable for manhole rings as per DIN 4034 part 2.

With Lifting Strap: SRG-UNI-1,5, SRG-UNI-3.

With High-tensile Lifting Chain: SRG-UNI-1,5-K, SRG-UNI-3-K, SRG-1,5, SRG-3, SRG-3-L.

- Manhole and Cone Chain Clamp SRG-UNI: especially easy handling and light-weight. Automatically adjustable clamping range of the claws to the thickness of the pipe walls.

SRG-UNI-1,5: for manhole rings as per DIN 4034, part 2 and cones.

SRG-UNI-3: for manhole rings as per DIN 4034, part 1 + 2 and cones.

| Type | Number of Claws Pcs. | Diameter Nominal Diameter mm (in) | Dead Weight kg (lbs) | Gripping Range mm (in) | Working Load Limit/WLL kg (lbs) | Order-Number |
|----------------------|----------------------|--------------------------------------|-------------------------|---------------------------|------------------------------------|-----------------|
| SRG-UNI-1,5 | 3 | 800 – 2,000 (31½ – 78¾) | 28 (60) | 40 – 120 (1½ – 4¾) | 1,500 (3,300) | 54400015 |
| SRG-UNI-1,5-K | 3 | 800 – 2,000 (31½ – 78¾) | 32 (70) | 40 – 120 (1½ – 4¾) | 1,500 (3,300) | 54400018 |
| SRG-UNI-3 | 3 | 800 – 2,000 (31½ – 78¾) | 40 (90) | 60 – 180 (2¼ – 7) | 3,000 (6,600) | 54400014 |
| SRG-UNI-3-K | 3 | 800 – 2,000 (31½ – 78¾) | 45 (100) | 60 – 180 (2¼ – 7) | 3,000 (6,600) | 54400019 |
| SRG-1,5 | 3 | 400 – 2,000 (15¾ – 78¾) | 31 (70) | 40 – 120 (1½ – 4¾) | 1,500 (3,300) | 54400001 |
| SRG-3 | 3 | 400 – 2,000 (15¾ – 78¾) | 55 (120) | 50 – 180 (2 – 7) | 3,000 (6,600) | 54400002 |
| SRG-3-L | 3 | 400 – 3,000 (15¾ – 118) | 58 (130) | 50 – 180 (2 – 7) | 3,000 (6,600) | 54400003 |