



RG-20/85-SAFELOCK



RG-75/125-SAFELOCK



RG-100/150-SAFELOCK

Round Grab RG-SAFELOCK

The clamping force of the claws is maintained fully in all cases, even if the carrier is operated incorrectly.

- Gripping and laying concrete pipes.
- Patented safety locking system: When lifting the product, the grab generates tension on the pipe, which is maintained even when the product is set down.
- One-man operation.
- With adjustable height supports, which can be adjusted with a scale using the external pipe diameter. This guarantees an optimum grab position.
- Slim design allows joint-sleeve pipes lying close together to be picked up onto the lorry loading area and used in very narrow trenches.
- With handles to guide the claw.
- The eye runs in a setting with 2 hanging positions. One is used for locked grabbing, the other for releasing the catch and for empty lifting. This allows operation with only one person.

RG-20/85-SAFELOCK: Increased grip width and increased working load limit as with RG-20/80.

Besides concrete pipes, **stoneware pipes** can also be laid.

Easy adjustment of the outer diameter by means of a scale and a central lock pin.

Rubber grippers.

Polyamide-coated height adjustment bracket.

Durable surface protection by galvanizing.

RG-75/125-SAFELOCK: Easy, continuous adjustment of the external diameter by means of a scale using threaded spindles. Crank included in the delivery.

Replaceable steel grab clamps with a reliable grip.

Optionally available: rubber gripper jaws to prevent surface damage.

Durable surface protection by galvanizing.

RG-100/150-SAFELOCK: Easy, continuous adjustment of the external diameter by means of a scale using threaded spindles. Crank included in the delivery.

Replaceable steel grab clamps with a reliable grip.

Type	Length of Gripper mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
RG-20/85-SAFELOCK	420 (16½)	175 (385)	200 – 870 (7¾ – 34¼)	2,500 (5,500)	54500009
RG-75/125-SAFELOCK	440 (17¼)	370 (820)	720 – 1,280 (28¼ – 50½)	4,000 (8,800)	54500005
RG-100/150-SAFELOCK	460 (18)	425 (940)	970 – 1,530 (38¼ – 60¼)	6,000 (13,200)	54500008