



TSZ-UNI with HVA-FTZ/TSZ



TSZ-UNI-WB-SQ

## Concrete Step Handles TSZ

Suitable for handling steps, kerb stones etc. in conjunction with a lifting device.

- Easily adjustable opening width by means of a spring-loaded bolt.
- Considerable inside height. Conical kerb stones are also gripped securely, as the gripper has an inside height of 185 mm (7¼ inch) thus being able to grip underneath the conical form.
- Lifting eye for attaching to crane hook.
- Automatic release for fully automatic switch-over from "full" to "empty".
- Exchangeable profiled rubber seals.
- Galvanised finish.

Type	Length of Gripper mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
<b>TSZ-UNI</b>	350 (13¾)	185 (7¼)	32 (70)	50 – 600 (2 – 23½)	600 (1,320)	<b>53100338</b>
<b>TSZ-MAXI</b>	350 (13¾)	185 (7¼)	35 (75)	850 – 1,100 (33½ – 43¼)	600 (1,320)	<b>53100364</b>

### Accessories

**TSZ-UNI-WB-SQ:** Special steelfinger grippers allow for safe installation of roughly-cut ashlar rocks. The steel-finger grippers can be screwed on the clamp in just a few simple steps for (all TSZ-UNI built in or after 2009, order number 53100338).

**TSZ-UNI-ET:** Fork sleeve with lifting eye and manual turning device, engaging every 90°. Thus the TSZ-UNI can be picked-up with the fork lift truck tines.

**Adjustable Height Stop HVA-FTZ/TSZ:** for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Adjustable range TSZ-UNI/MAXI approx. 55 – 140 mm (2¼ – 5½ inch). Adjustable range FTZ-UNI/MAXI-25 and FTZ-UNI/MULTI-15 approx. 120 – 255 mm (4¾ – 10 inch).

FTZ-UNI-50 approx. 55 – 155 mm (2¼ – 6¼ inch). FTZ-MAXI-50 approx. 55 – 195 mm (2¼ – 7¾ inch).

Type	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
<b>TSZ-UNI-WB-SQ</b>	210 (8¼)	5.58 (10)	50 – 550 (2 – 21¾)	600 (1,320)	<b>43101384</b>
<b>TSZ-UNI-ET</b>		25 (55)		600 (1,320)	<b>43101130</b>
<b>Adjustable Height Stop HVA-FTZ/TSZ</b>		2.5 (6)			<b>43100867</b>