



FTZ-UNI-15



FTZ-MAXI-25

Grab for Prefabricated Concrete Products FTZ

FTZ-I: special compact clamp for laying heavy granit kerbs.

FTZ-BB: designed kerb stones with high concave section for bus stops („Kassel Kerb“).

FTZ-UNI: Universal clamp for all kind of precast elements.

FTZ-MAXI: As FTZ-UNI but with a very large gripping range.

- Gripping width adjustment by spring loaded bolt. Bolt can not get lost.
- Suspension bolt for lifting device.
- Automatic release for fully automatic switch over from „full“ to „empty“.
- Exchangeable rubber grippers.
- With handles to guide the grab.
- Durable surface protection by galvanizing.

Type	Length of Gripper mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
FTZ-I	420 (16½)	170 (6¾)	55 (120)	50 – 520 (2 – 20½)	900 (1,980)	53100120
FTZ-BB	420 (16½)	290 (11½)	60 (130)	50 – 480 (2 – 19)	900 (1,980)	53100202
FTZ-UNI-15	420 (16½)	255 (10)	88 (195)	0 – 750 (0 – 29½)	1,500 (3,300)	53100256
FTZ-UNI-25	420 (16½)	255 (10)	119 (260)	0 – 750 (0 – 29½)	2,500 (5,500)	53100313
FTZ-MAXI-25	420 (16½)	255 (10)	132 (290)	200 – 1,200 (7¾ – 47¼)	2,500 (5,500)	53100344
FTZ-UNI-50	720 (28¼)	200 (7¾)	245 (540)	0 – 850 (0 – 33½)	5,000 (11,000)	53100362
FTZ-MAXI-50	720 (28¼)	240 (9½)	260 (570)	400 – 1,250 (15¾ – 49¼)	5,000 (11,000)	53100363

Accessories:

Adapter for Kassel Kerb Stone A-FTZ-KB: for FTZ-UNI-15 to extend gripping depth on one side to 290 mm (11½ inch).

Adjustable Height Stop HVA-FTZ/TSZ: for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Adjustable range TSZ-UNI/MAXI approx. 55 – 140 mm (2¼ – 5½ inch). Adjustable range FTZ-UNI/MAXI-25 and FTZ-UNI/MULTI-15 approx. 120 – 255 mm (4¾ – 10 inch).

FTZ-UNI-50 approx. 55 – 155 mm (2¼ – 6¼ inch). FTZ-MAXI-50 approx. 55 – 195 mm (2¼ – 7¾ inch).

Type	Dead Weight kg (lbs)	Order-Number
Adapter for Kassel Kerb Stone A-FTZ-KB	6.9 (15)	43100575
Adjustable Height Stop HVA-FTZ/TSZ	2.5 (6)	43100867