

**NEW**

**SAFLOK® CONCRETE WEDGE ANCHOR**



**Extremely Versatile  
and Easy-to-Use  
Anchor for  
Concrete Applications**

**Portable**

**Reusable**

**Durable**

**Safe**



# SAFLOK® CONCRETE WEDGE ANCHOR



## Complete Versatility and Flexibility

The anchor was designed with strength and flexibility in mind. It is 22kN rated, and an ideal connection point for a personal fall arrest system, work positioning system, personnel riding system or rescue system. In addition, a truly "compatible" connection ring unlike any other on the market makes tying off to this device safe and secure.

## Extremely Easy Installation and Removal

Installation is simple and efficient, taking just seconds utilising a standard concrete drill and drill bit.

- Drill a 76mm deep hole with rotary hammer and 19mm drill bit.
- Pull up on the trigger until it's fully retracted.
- Insert anchor into hole until the release plug seats against concrete surface, then release the trigger.
- Pull on the D-ring to set the anchor in place and connect your personal fall arrest system.

Release of the anchor is just as fast. Simply push the release plug down and pull up on the trigger and your ready to move to the next location.



## Anchorage Requirements

The concrete must have a minimum compressive strength of 21MPa. The concrete base material must be at least 127mm thick and the mounting hole location from the edge is dependent upon the concrete thickness and width (refer to instruction manual for complete details).

## Specifications:

**Hole Size:** 19mm. **Capacity:** 22kN. **Rating:** Single user fall protection up to 141kg. **Weight:** 0.354kg. **Cable Material:** Galvanised Steel. **Anchor Chocks & Shaft Material:** Stainless Steel. **Release Plug Material:** Zinc Plated Steel. **Trigger Material:** Aluminium. **D-Ring Material:** Forged Steel. **Compatibility:** DBI-SALA anchors are designed for use with DBI-SALA approved components and systems, or as recommended by a competent person. **Standards:** Complies with AS/NZS 1891.4. **Country of Origin:** United States. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. Annual inspection and re-certification is required as per AS/NZS 1891.4:2000. The lanyard and lines should always apply the load in shear, not in direct pull out.



← **Swiveling Forged Steel Ring for Compatible and Safe Connections**

**22kN Fall Arrest Rated for Ultimate Security**  
(See Special Instructions Below)

**Use Vertically or for Overhead/Ceiling Applications for Added Versatility**

← **Easy-Grip Trigger for Fast and Easy Operation**

← **Quick-Release Plug Provides Easy Release and Removal for Added Productivity**

← **Shielded Retractor Cables Protects Against Damage**

**Corrosion Resistant Stainless Steel and Aluminum Construction**

← **Conical Wedge Chocks Provide Superior Grip**

## Saflok® Concrete Wedge Anchor Models:

**2100085:** Saflok® Concrete Wedge Anchor

## Capital Safety:

Australia: 1800 245 002 New Zealand: 0800-212 505 Asia: +852 2992 0381  
USA: 800-328-6146 Canada: 800-387-7484 Northern Europe: +44 (0) 1928 57 1324  
Europe, Middle East & Africa: +33 (0) 497 10 00 10 Or visit: [WWW.CAPITALSAFETY.COM](http://WWW.CAPITALSAFETY.COM)