

## Vector fall arrester

D23

**A versatile, multi-functional fall arrest and work positioning rope device designed specifically for roof work and ladder climbing.**

The Vector is designed for fall arrest when used on a vertical rope and for work restraint when used on level or sloping ground.

Designed to be used on 10.5-11.0 mm diameter low stretch rope the Vector moves up and down freely with the user, allowing a high degree of flexibility whilst working.

For maximum ease of movement and safety, we recommend attachment with a short extension link (e.g. 35 cm including connectors).

Satisfies requirements of both EN 353-2 (vertical fall arrest) and EN358 (work positioning) standards.

Key features:

- Multi-functional – fall arrest, work positioning
- Can be loaded onto the rope at any point
- Moves freely up and down vertical line
- Self-locking cam
- Supremely simple to use
- Easy to inspect and maintain – all component parts are visible
- Individually marked for traceability
- Anodised aluminium and stainless steel construction

NB: This device is not designed for two person loads therefore not suitable for rope access.

Rope diameter 10.5 mm to 11.0 mm



### Specifications:

Size:

EN Test Mass: 125 kg

Loading:

Conformity: EN353-2, EN358

Materials: Anodised aluminium and stainless steel construction

Weight (kg): 0.24

Industries: Roof Access, Ladder Climbing