



TECHNICAL SHEET FA 10 110 00

FIRE FREE HARNESS

FIRE FREE



This harness has been designed to offer a perfect solution for workers doing welding at height. We recommend its use for shipbuilding, building steelwork...

Attachment points: 1 dorsal D-Ring (A) ●, 2 chest attachment textile loops (A/2) ● for fall arrest.

Adaptability: Adjustable shoulder and thigh straps.

Convenience: Static strength of the harness webbing has been tested after being exposed to the small molten metal splashes. Automatic buckles on thigh straps.

Ergonomics: Ideally positioned sit-strap for extended comfort.

Compliance: Complies with the standards EN 361:2002, ISO 9150: 988 and ISO 15025:2005.

Identification and verification tracking labels protected by an openable cover. The name of the user can be written on the cover.

Material of components:

Webbing: aramid.

Buckles: steel.

Size:	CE	Weight:
Universal		1.79 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigue
69780 Saint Pierre de Chandieu – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

63072090

CARTON SIZE / PCS.

60 x 40 x 48 cm / 08

AET N°2342 ISSUE 10 EXTENSION 14

Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom