

VORAS F2




- Retractable fall arrester with a 50 mm webbing.
- Incorporate a protective casing and an energy absorber (45 mm).
- Fall indicator at the top of the device
- Minimum breaking strength > 15 kN.

Connector :

1 snap hook, opening 17 mm FA 50 202 17.

Compliance : Conforms to EN 360:2002 that can be used in fall factor 2 (maxi 1.80 m).


Material of components :

Casing : Polyethylene anti choc
 Webbing : Polyamide / Polyester
 Connector : Steel

Length :	CE	Weight :
2 m		1.35 kg

KRATOS SAFETY

689 Chemin du Buclay
 38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

8428 90 90

CARTON SIZE / PIECES

60 x 40 x 24 / 10

AET N°2194 Issue 5 Extension 3

Satra Technology Centre, N°0321
 Wyndham Way, Telford Way, Kettering
 Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
 Unit 202B, Worle Parkway,
 Weston-super-Mare, BS22 6WA, United Kingdom