



# TECHNICAL SHEET FA 20 401 30

## WIRE ROPE RETRACTABLE FALL ARRESTER WITH INTEGRATED RESCUE WINCH, LENGTH 30 M



- Comes with Galvanized Steel Wire Rope of diam. 4.5 mm.
- Casing made up of high impact strength Polymer, to prevent breakage.
- Swivel at the top and connector at the bottom of the device.
- Internal braking mechanism to reduce the fall arrest force to less than 6kN.
- Integrated recovery system.
- The device can be adapted on our TRIPOD (FA 60 001 00 or FA 60 002 00) through the Kit FA 60 001 02, as well as on MultiSafeWay (FA 60 022 00) through the plate FA 60 022 03.

**Minimum breaking strength > 12 kN.**

- **Connectors:** Swivel and steel screw-locking karabiner FA 50 101 17, opening 18 mm, at anchorage end, and steel snap hook FA 50 203 20, opening 20 mm, with swivel and load indicator at attachment end.

**Maxi weight for vertical use: 140 kg.**

**Compliance:** Conforms with EN 360:2002 and EN 1496:2006 Class B.

**Material of components:**

Protective casing: PA 6 30% fiberglass  
 Wire rope: Galvanized steel  
 Connectors: Steel

|          |           |          |
|----------|-----------|----------|
| Length : | <b>CE</b> | Weight : |
| 30 m     |           | 14.80 kg |

**KRATOS SAFETY**  
 689 Chemin du Buclay  
 38540 HEYRIEUX – FRANCE

Tel : +33 (0)4 72 48 78 27  
 Fax : +33 (0)4 72 48 58 32  
[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

|  |
|--|
| <b>HS CODE</b>   |
| 8428 90 90   |
| <b>CARTON SIZE / PIECES</b>  |
| 60 x 40 x 30 cm / 1  |
| <b>AET N°7426 Issue 4 Extension 2</b>  |
| Satra Technology Centre, N°0321<br>Wyndham Way, Telford Way, Kettering<br>Northamptonshire, NN16 8SD, United Kingdom |
| <b>ARTICLE 11 GB07/73551</b>   |
| SGS United Kingdom Ltd., N°0120<br>Unit 202B, Worle Parkway,<br>Weston-super-Mare, BS22 6WA, United Kingdom          |