



TECHNICAL SHEET



FA 20 501 02


Designation : Retractable Fall Arrester Olympe in webbing

- Width of the webbing : 25 mm
- Casing made up of high impact strength Polymer to prevent breakage and nearly indestructible.
- Having a swivel arrangement at anchorage end.
- Minimum breaking strength : > 15 kN.

Connectors:

1 steel screw-locking karabiner, opening 17 mm ref. FA 50 101 17 and 1 steel snap hook with swivel and fall indicator, opening 21 mm.

Compliance : Conforms to EN 360:2002



Length: 2 mtrs.

Material of the components:

Casing: Polyethylene anti shock
Webbing: Polyester
Connectors: Steel

HS code	Carton size / Pieces	Unit weight
84289090	60x40x24 cm / 05	1.44 Kg

AET : N° 6463 Issue 1 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 01/15

ZI les portes du Dauphiné

4 rue de l'Aigue
69 780 St Pierre de Chandieu – France
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
www.kratossafety.com info@kratossafety.com

