



FICHE TECHNIQUE

FA 30 303 15

Designation :

Energy absorbing webbing lanyard

- Energy absorber in 44mm wide webbing which reduces the impact of the fall less than 6 KN
- 44mm wide polyester webbing lanyard
- Loops protected by an abrasion resistant tubular webbing

Connectors :

1 steel scaffold hook, opening 55 mm, ref. FA5020755 and 1 steel snap hook, opening 17 mm, ref. FA5020217

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/CEE



Length :

Lg : 1.5 mtr (connector included))

Materials :

Lanyard : polyester

Absorber : polyester and polyamide

Connector : steel

HS code

56090090

Dimension carton/ UC

67x38x24 / 25

Poids unitaire

1.10 Kg

AET: N° 4301 Issue 2 Extension 4

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 07/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

