



# TECHNICAL SHEET

FA 30 305 10



**Designation:** FIRE FREE Energy Absorbing Webbing Lanyard

Designed to offer a perfect solution for workers doing welding at height. We recommend its use for: shipbuilding, building steelwork, ...

- Energy absorber in 44mm wide webbing which reduces the impact of the fall to less than 6 KN.
- Aramid webbing lanyard width 45 mm.
- Energy Absorber covered by a non fire fabric.

**Connectors:**

1 steel scaffold hook, opening 55 mm, ref. FA 50 207 55 and 1 steel screw-locking karabiner, opening 17 mm, ref. FA 50 101 17.

**Compliance:**

EN355 : 2002 and tested as per VG11 - 89/686/CEE, ISO9150 : 1988 and ISO15025 : 2005.

**Length :** 1 m (connectors included)


Also exists in 1.5 and 2 m.

**Materials:**

Lanyard: aramid

Absorber: polyester and polyamide

Connectors: steel



**HS code**

56090090

**Carton Size / Pieces**

60x40x24 / 20

**Unit Weight**

1.08 Kg

**AET: N° 4301 Issue 6 Extension 2**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 06/14

**ZI les portes du Dauphiné**

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) [info@kratossafety.com](mailto:info@kratossafety.com)

