



TECHNICAL SHEET

FA 30 306 20



Designation:

Energy Absorbing Webbing Lanyard

- 44 mm wide webbing Energy Absorber which reduces the impact of the fall less than 6 KN
- Lanyard in polyester webbing, width 44 mm

Connectors:

1 aluminium scaffold hook double action, opening 60 mm, ref. FA 50 208 60 and 1 aluminium screw-locking karabiner, opening 22 mm, ref. FA 50 103 22.

Compliance:

EN355 : 2002, EN1149-1 : 2006 (surface resistivity) and ATEX Directive 94/9/CE, EN13463-1 (2001) and EN136463-5 (2006).

Length:

Lg: 2 mtrs (connectors included)

Materials:

Lanyard: polyester with antistatic properties

Absorber: polyamide and polyester with antistatic properties

Connectors: aluminium



HS code

56090090

Carton Size / Pieces

60x40x24 / 25

Unit Weight

0.95 Kg

AET: N° 4301 Issue 6 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 07/14

ZI les portes du Dauphiné
4 rue de l'Aigue
69 780 St Pierre de Chandieu – France
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
www.kratossafety.com info@kratossafety.com

