



TECHNICAL SHEET FA 30 309 20

REVOLTA – EXPANDABLE ENERGY ABSORBING WEBBING LANYARD

REVOLTA

SERIES



Length:	CE	Weight:
1.5 m to 2 m		1.68 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigue
69780 Saint Pierre de Chandieu – FRANCE

Tel.: +33 (0)4 72 48 78 27

Fax: +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

- Energy absorber in webbing with central weaving with progressive deformation, which reduces the impact of the fall to less than 6kN.
- 45 mm wide Polyester expandable/elasticated webbing lanyard with oil and dirt repellent coating. Highly UV resistant for increased durability and longevity.



- Expanded length: 2 m / Relaxed length: 1.50 m.
- Loops protected by an abrasion resistant tubular webbing.

Connectors:

1 aluminium rebar hook FA 50 208 60, opening 60 mm and 1 aluminium snap hook FA 50 212 21, opening 21 mm.

Compliance : EN355 : 2002.

Material of components:

Lanyard: Polyester, with water, oil and dirt-repellent treatment.

Absorber: Polyester and Polyamide

Connectors: Aluminium

HS CODE
6307 90 98
DIMENSIONS CARTON / UC
60 x 40 x 24 cm / 25
AET N°6174 I3 1E
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom