



TECHNICAL SHEET



FA 30 403 15

Designation:

Forked Energy Absorbing Webbing Lanyard

- 44 mm wide webbing Energy Absorber, which reduces the impact of the fall less than 6 KN.
- Lanyard in polyester webbing, width 44 mm.

Connectors:

2 aluminum scaffold hooks double action, opening 60 mm, ref. FA 50 208 60 and 1 aluminum screw-locking karabiner, opening 22 mm, ref. FA 50 103 22.

Compliance:

EN355:2002 and tested according VG11 requirements - 89/686/CEE EN1149-1:2006 (surface resistivity) and ATEX Directive 94/9/CE, EN13463-1 (2001) and EN136463-5 (2006).



Length:

Lg: 1.5 m (connectors included).

Materials :

Lanyard: polyester with antistatic properties.
Absorber: polyamide and polyester with antistatic properties.
Connectors and buckles: aluminium.

HS code	Carton Size/ Pieces	Unit Weight
56090090	40x40x24 / 10	1.47 Kg

AET : N°4304 Issue 6 Extension 1

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ: 07/2014

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

