



# TECHNICAL SHEET FA 30 405 15

## FORKED DIELECTRIC ENERGY ABSORBING WEBBING LANYARD, LG. 1.50 M



Dielectric webbing lanyard with an energy absorber, designed to protect operators working in an environment with potential dielectric hazards.

- Energy absorber in 44 mm wide webbing, which reduces the impact of the fall to less than 6kN. Energy absorber with a fall indicator:



Black sleeve for increased longevity and UV-resistance.

- 30 mm wide polyester webbing.

**Connectors:** 1 dielectric snap hook, gate opening 15 mm, FA 50 223 15 at the absorber end, and 2 dielectric rebar hooks, gate opening 55 mm, FA 50 222 55, at the other end.

**Compliance :** EN355:2002.

### Material of components:

Webbing: Polyester

Absorber: Polyester and Polyamide

Connectors: Steel with insulating polymer composite that can withstand a maximal voltage of 14 kV.

<b>Length:</b>	<b>CE</b>	<b>Weight:</b>
1.50 m		2.03 kg

### **KRATOS SAFETY**

689 Chemin du Buclay,  
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27  
Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

<b>HS CODE</b>
5609 00 90
<b>CARTON SIZE / PIECES</b>
80 x 40 x 24 cm / 10
<b>AET N°4304 I8 E</b>
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>ARTICLE 11 GB07/73551</b>
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom