



TECHNICAL SHEET

FA 30 500 15

Designation:

Energy Absorbing Kernmantle Rope Lanyard composed of:

- Energy absorber in 44 mm wide webbing, which reduces the impact of the fall to less than 6 kN,
- 12 mm diam. polyamide Kernmantle rope lanyard,
- Loops protected by an abrasion resistant thimble,
- Sewing protected with strong transparent covering sleeve.

Compliance:

EN355 : 2002 and tested as per VG11 - 89/686/EEC.

Length:

Lg: 1.5 m.

Materials:

Lanyard: Polyamide.

Energy absorber: Polyester and Polyamide.



HS code

56090090

Carton Size / Pieces

60x40x24 / 25

Unit Weight

0.39 kg

AET: N° 4334 Issue 2 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 07/14

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

