



# TECHNICAL SHEET

FA 30 502 15

**Designation:** Energy absorbing kernmantle rope lanyard

- Energy absorber in 35mm wide webbing, which reduces the impact of the fall (less than 6 KN).
- 12mm diam. polyamide Kernmantle rope lanyard.
- Loops protected by an abrasion resistant thimble.
- Spliced end protected with strong covering sleeve.

**Connector:**

1 steel scaffold hook, opening 55 mm, ref. FA 50 207 55.

**Compliance:**

EN355:2002 and tested as per VG11 - 89/686/CEE.



**Length :**

Lg: 1.5 m (connectors included).

**Materials:**

Lanyard : polyamide

Absorber : polyester and polyamide

Connector : steel

**HS code**

56090090

**Carton size / Pieces**

60 x 40 x 24 / 25

**Unit weight**

0,85 kg

**AET : N° 4334 Issue 2 Extension 4**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 10/14

**ZI les portes du Dauphiné**

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

