



## TECHNICAL SHEET FA 30 512 20

KERNMANTLE ROPE LANYARD WITH ENERGY ABSORBER, LGTH. 2 MTRS

**gravity-s**



- Energy absorber in 35mm wide webbing which reduces the impact of the fall to less than 6 KN. Energy absorber equipped with a fall indicator:



- Black sleeve for a better UV resistance.
- 12 mm diam. polyamide Kernmantle rope lanyard, specially designed to withstand sharp edges.



- Loops protected by an abrasion-resistant thimble.
- Sewing protected with strong transparent covering sleeve.

### Connectors:

1 aluminium scaffold hook, opening 60 mm (FA 50 218 60) and 1 aluminium screw-locking karabiner, opening 22.5mm (FA 50 105 22B).

**Compliance:** EN355:2002, and tested as per VG11 of PPE Directive 89/686/EEC.

### Material of components:

Lanyard: Polyamide Kernmantle rope

Absorber: Polyester and Polyamide

Connectors: Aluminium

Length:	CE	Weight:
2 mtrs		0.79 kg

### KRATOS SAFETY

ZI les Portes du Dauphiné  
4, rue de l'Aigue  
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### HS CODE

5609 00 90

### CARTON SIZE / PIECES

60 x 40 x 24 cm / 20

### AET N° I E

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom