



# TECHNICAL SHEET

FA 30 514 20



**Designation :** Energy absorbing kernmantle rope lanyard with ring adjuster

- Energy absorber in 35 mm wide webbing which reduces the impact of the fall to less than 6 KN.
- Black protective sleeve for increased longevity and UV resistance.
- Has a fall indicator label.
- 12mm diam. Polyamide kernmantle rope lanyard, with ring adjuster.
- Loops protected by an abrasion resistant thimble.
- Spliced end protected with strong covering sleeve.

**Connectors:**

1 aluminum scaffold hook opening 60 mm, ref. FA 50 218 60 and 1 aluminum screw-locking karabiner opening 22 mm, ref. FA 50 105 22B.

**Compliance:** EN 355:2002.



**Length:**

Lg: maximum 2 mtrs (connectors included)

**Materials:**

Lanyards: polyamide  
Absorber: polyester and polyamide  
Connectors: aluminum  
Ring adjuster: Steel

**HS code**

56090090

**Carton Size/ Pieces**

60x40x24 cm / 20

**Unit weight**

1.01 Kg

**AET N°4334 Issue 5 Extension 1**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 02/17

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

