











HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N° 2777/10963-02/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland



REF.	FA 30 522 10	FA 30 522 15	FA 30 522 20
LG.  KG	1 m (connector included)	1.5 m (connector included)	2 m (connector included)
	100 KG	140 KG	
CE	EN 335:2002		
MAT.	 PA 11 mm Polyamide		
	35 mm		
	 FA 50 103 22 / FA 50 208 11		
	NO		
+	---		
	1.01 KG	1.05 KG	1.10 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
Ancho del absorbedor de energía
 Larghezza del assorbitore di energia
Breite des Falldämpfers



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteurs
 Material of connectors
Material de los conectores
 Materiale connettori
Material Verbinder



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten