



TECHNICAL SHEET

FA 30 610 15

Designation: Forked Kernmantle rope energy absorbing lanyard

- Webbing energy absorber, width 44 mm, which reduces the impact of the fall to less than 6 kN.
- 12 mm diam. Polyamide Kernmantle rope lanyard.
- Loops protected by an abrasion resistant thimble.
- Spliced end protected with strong covering sleeve.

Connectors:

2 aluminium rebar hooks opening 60 mm, ref. FA 50 218 60, and 1 aluminium screw-locking karabiner opening 22 mm, ref. FA 50 105 22.

Compliance:

EN355 : 2002 and tested as per VG11 - 89/686/CEE.



Length:

Lg 1,5 m (connectors included).

Materials:

Lanyards : Polyamide
Absorbers : Polyester and polyamide
Connectors : Aluminium

HS code

56090090

Carton Size / Pieces

40x40x24 / 10

Unit weight

1.65 Kg

AET : N° 4333 Issue 5 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 01/15

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

