



TECHNICAL SHEET

FA 30 614 20

Designation :

Forked energy absorbing kernmantle rope lanyard

- Energy absorber in 44mm wide webbing which reduces the impact of the fall less than 6 KN
- 12mm diam polyamide kernmantle rope lanyard
- Loops protected by an abrasion resistant thimble
- Spliced end protected with strong covering sleeve
- Ring Adjuster on each lanyard

Connectors :

2 aluminium scaffold hooks opening 60 mm and 1 aluminum screw-locking karabiner opening 22 mm, ref. FA 50 105 22.

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/CEE



Length :

Lg : maximum 2 mtrs (connectors included)

Materials :

Lanyards : polyamide

Absorber : polyester and polyamide

Connectors : aluminum

Ring Adjusters : Steel

HS code

56090090

Carton Size/ Pieces

60x40x24 / 25

Unit Weight

1.88 Kg

AET : N° 4333 Issue Extension

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 08/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

