

Designation :

Energy Absorbing Expandable Webbing Lanyard

- Energy Absorbing in webbing, width 35 mm, which reduces the impact of the fall to less than 6 kN
- 44 mm wide polyester expandable elasticated webbing lanyard.
- Loops protected by an abrasion resistant tubular webbing.

Connector :

1 steel scaffold hook, opening 55 mm, ref. FA5020755

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/CEE



Length :

Expanded length : 1.8 m

Relaxed length : 1.4 m

Materials :

Lanyard : polyester

Absorber : polyester and polyamide

Connector : steel

HS code

56090090

Carton size / Pieces

67x38x24 / 25

Unit Weight

0.87kg

AET: N° 4332 Issue 1 Extension 3

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 11/14

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

