



TECHNICAL SHEET

FA 30 900 20

Designation :

Energy Absorbing Elasticated Webbing Lanyard

- Energy Absorber in webbing with central weaving and progressive deformation which reduces the impact of the fall to less than 6 kN
- Elasticated webbing lanyard in polyester width 44 mm

Connectors :

1 aluminium screw-locking karabiner opening 22 mm,
Ref. FA 50 105 22 and 1 aluminium scaffold hook, opening 60 mm

Compliance : EN355 : 2002

Size :

Expanded Length : 2 mtr

Relaxed length : 1.4 mtr

Materials :

Lanyard : polyester

Absorber : polyester and polyamide

Connectors : aluminium



HS code

56090090

Carton Size / Pieces

67x38x24 / 25

Unit Weight

0.95 Kg

AET : N° 6174 Issue 1 Extension 1

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 05/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

