



# TECHNICAL SHEET FA 40 503 10

## RESTRAINT KERNMANTLE ROPE LANYARD



### Restraint Kernmantle Rope Lanyard

- Made up of 12mm diam polyamide kernmantle rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Sewing protected with a strong transparent covering sleeve which protects the ends and also make stitches visible for easy inspection before the use.
- Résistance à la rupture : 22 kN

### Connectors:

1 steel snap hook opening 17 mm, ref FA5020217, and 1 steel scaffold hook, opening 55 mm, ref. FA5020755

**Compliance :** EN354 : 2002

### Material of components:

Lanyard : polyamide

Connector : steel

<b>Size:</b>		<b>Weight:</b>
1 mtr		0.84 kg

### KRATOS SAFETY

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### HS CODE

56075090

### CARTON SIZE / PCS.

60 x 40 x 24 / 25

### AET N°2577 I2 E5

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom