



TECHNICAL SHEET FA 40 907 20

REVOLTA Adjustable work positioning lanyard

REVOLTA

SERIES



Length:	CE	Weight:
Maxi 2 m		0.73 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

Ideal for use in: a variety of applications including petrochemical, painting, water treatment, food processing, offshores, general industry...

- Made of 44mm wide oil and dirt repellent webbing incorporated with 50mm tubular webbing sleeve for abrasion resistance.
- Highly UV resistant. Increased durability and longevity.
- **Max. length:** adjustable up to 2m.
- Two Aluminium snap hooks, opening 21 mm (ref. FA 50 212 21).

Material of components:

Adjustment buckle: Steel

Connectors: Aluminium

HS CODE
56090090
CARTON SIZE / PC.
60 x 40 x 24 cm / 25
AET N°8148 I1 E1
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom