



# TECHNICAL SHEET FA 60 002 00

## 10 ft. Tripod



10 ft. Tripod for access in confined spaces

- With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable.
- Having two auxiliary eye bolts as attachment points.
- Aluminum alloy cast head, legs in aluminum.
- Steel support-shoes provided with rubber sole to increase friction and impart more stability.
- Strength of anchorage point greater than 12 kN
- Every Tripod is provided with inbuilt fixture for attaching our winch FA 60 003 00 (can be supplied without this fixture on special request).
- Every Tripod is provided with Tripod Bag

**Compliance:** Conforms to EN 795:2012 Type B

### Specifications:

- Fully adjustable telescopic legs, adjustable height from 1.90 m to 2.90 m.
- Wheelbase: 1.52 m to 2.05 m.
- **Maximum load capacity:** 500 kg.

### Material of components:

Aluminium legs  
Steel support shoes

Adjustable height:		Weight:
From 1.90 m to 2.90 m		15 kg

### KRATOS SAFETY

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27  
Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### HS CODE

76109010

### CARTON SIZE / PCS.

210 x 30 x 28 cm / 1

### AET N°2129 I3 E3

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom