




Dielectric Beam Anchor Trolley

Designed to protect operators working in an environment with potential electric hazards.

The wheels are made of electrically insulated rollers thank to a special polymer that can withstand a maximal voltage of 30 kV.

Maximum dielectric resistance: 30 kV.

Webbing length: 170 mm.

Dimensions: Designed to be installed on beams whose width can vary from 80 to 250 mm.

Compliance: Conforms to EN795:2012 Type B.

Static strength: 12 kN.

Minimum breaking strength: > 23 kN.

Material of components:

Aluminium and Stainless steel

	Weight: 3.70 kg
---	---------------------------

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

83081010

CARTON SIZE / PCS.

60 x 40 x 24 cm / 2

AET (EU) N° 2777/10796-02/E01-01

Satra Technology Europe Ltd, N° 2777,

Bracetown Business Park, Clonee,
Dublin, D15YN2P, Ireland

MODULE D IN14/14003

SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom