



TECHNICAL SHEET



FA 60 017 15

Designation:

FIRE FREE anchorage webbing lanyard

Designed to offer a perfect solution for workers doing welding at height. We recommend its use for: shipbuilding, building steelwork,...

- Aramid webbing Lanyard width 44 mm
- Steel D-rings on both ends

Minimum breaking strength: > 15 kN


Compliance: EN795:2012 Type B, ISO9150:1988 and ISO15025:2005.

Length: 1.5 m

Materials:

Lanyard: aramid

D-rings: steel



HS code

56090090

Carton Size / Pieces

60x40x24 / 50

Unit Weight

0.36 kg

AET : N°2598 Issue 7 Extension 3

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 07/14

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

