



TECHNICAL SHEET FA 60 026 00

EDGE ANCHOR



Edge anchor

- Multi-depth adjustments to suit varying roof cladding profiles.
- Must be fitted on steel box profile type roofs with a maximum profile height of 29 mm.
- Designed for single user only.
- Easy storage and transport.
- Light in weight and robust.
- Having energy absorbing arm with fall indicator it provides additional safety to the user while working.

- **Minimum Breaking (System) Strength: 15 kN.**

Compliance: EN 795:2012 Type B.

Material of components:

High Strength Aluminium Alloy
Steel

CE	Weight:
	3.0 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigue
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax. : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

7616 90 10

CARTON SIZE / PIECES

80x40x32cm / 6

AET N° I E

Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom