

**Ex** II 2 G Exh IIC T6 Gb  
ZONE 1



REF. FA 20 704 00



REF. FA 20 708 00



REF. FA 20 703 00



REF. FA 20 706 00

OR



REF. FA 20 706 01



REF. FA 20 700 00

REF. FA 20 701 00



REF. FA 20 702 00







REF. FA 20 707 00



		689 CHEMIN DU BUCLAY LIEU-DIT LA MURIÈRE 38540 HEYRIEUX - FRANCE TEL : +33 (0)4 72 48 78 27			
INSTALLED BY					
PRODUCT / SYSTEM					
STANDARD / NORM					
BATCH AND YEAR OF MANUFACTURE					
LENGTH (in M)		CLEARANCE:			
INSTALLATION DATE / REFERENCE				MAXIMUM NUMBER OF USERS:	
ACCEPTANCE DATE					
INSPECTION DATE					

REF. FA 20 902 00

<b>HS CODE</b>
73269099
<b>AET N° 2777/10981-01/E01-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>ACKNOWLEDGEMENT OF RECEIPT N°3975/1/2018 (ATEX)</b>
<b>Technická Inšpekcia, a.s. N°1354</b> Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika

<b>REF.</b>	KS 9000
<b>LG.</b>  <b>KG</b>	----- MAX. 100 KG
<b>CE</b>	EN 353-1
<b>MAT.</b>	
<b>R (kN)</b>	15 kN
<b>+</b>	ATEX directive 2014/34/UE  II2 G Exh IIC T6 Gb <b>ZONE 1</b>
	---



**Longueur** Poids maxi utilisateur  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers

### R(kN)

**Résistance (en kN)**  
 Resistance (kN)  
**Resistencia (en kN)**  
 Resistenza  
**Belastbarkeit (in kN)**