

The **G.Tripod** is a quality anchorage device that is both durable and versatile. It is designed to provide a secure and stable anchorage for confined space access and down-hole applications.

The G.Tripod is setup over a horizontal aperture and can be used alongside our G.Saver II, G.Winch and G.Stop products to provide a secure and stable anchorage. When used with the G.Saver II, the G.Tripod protects personnel descending into or leaving a confined space. When used with the G.Winch it can be used to lower and raise personnel.

The G.Tripod has been manufactured using tubular aluminium for lightness and long term durability. The legs are telescopic and can be adjusted to allow safe use on uneven surfaces. The legs fold easily to aid transport and storage of the tripod. Rubber cup feet ensure stability of the G.Tripod in a wide variety of working environments.

The G.Tripod can also be supplied with brackets to suit the G.Saver II, G.Stop and G.Winch.



G.Tripod with  
G.Saver II and  
G.Winch fitted

### Features

- ◆ Manufactured in the UK
- ◆ Tubular aluminium (robust and lightweight)
- ◆ Twin pulley option (two devices can be mounted in tandem)
- ◆ Spans up to 1.75m diameter aperture
- ◆ Simple folding design
- ◆ 136kg safe working load
- ◆ Weight: 18kg (excl. brackets)
- ◆ CE certified, fully tested to European standards. Conforms to EN795

**Max height:** 2.4m

**Leg span diameter (max):** 2.25m

**Length when closed:** 1.7m

#### Compatible with:

G.Saver II

G.Stop

G.Winch



Globestock Limited, Mile Oak Industrial Estate  
Maesbury Road, Oswestry, Shropshire, SY10 8GA. UK

T: +44 (0) 1691 654 966 F: +44 (0) 1691 661 726  
info@globestock.co.uk www.globestock.co.uk @Globestock\_Ltd

PL: 10, Issue: 04. Globestock Ltd reserve the right to change specifications without prior notice. © Globestock 2016.