



# G.Saver II™

Fall Arrester & Rescue Winch

GSE407-434

The G.Saver II is a retractable fall arrest device which features a combined rescue winch for raising or lowering the user to safety, should a fall occur.

The G.Saver II should be primarily used in fall arrest mode with the winch mechanism disengaged, in order to protect the user from a fall. Should a fall occur, the steel cable is pulled out at an accelerating rate; when a speed of 1.5m/sec is reached, the braking system activates, thereby arresting and cushioning the fall. Once the fall has been arrested, the winch mechanism can be engaged so that the user can be either raised or lowered to safety. The G.Saver II eliminates the need for additional equipment to retrieve users and prevents them from being suspended for a long period of time, awaiting rescue by other means.

With the suspended load removed and the winch mechanism disengaged, the cable automatically retracts back in to the unit, regaining its fall arrest function.

The G.Saver II can be mounted vertically above the user or horizontally, in conjunction with a suitable anchorage point. It can also be used in conjunction with our G.Tripod.



## Features

- Manufactured in the UK
- Retrieval winch with anti-run brake
- Shock absorbing brake mechanism
- Galvanised or stainless steel cables available
- Cable lengths of 7 to 34m available
- Cable retrieval rate: approx. 3m per minute
- Stopping distance of approx. 0.6m to 1.0m
- 136kg safe working load
- Weight: 11-23kg (cable length dependant)
- CE certified, fully tested to European standards. Conforms to EN360 & EN1496



Globestock® Limited, Mile Oak Industrial Estate  
Maesbury Road, Oswestry, Shropshire, SY10 8GA. UK

T: +44 (0) 1691 654 966 F: +44 (0) 1691 661 726  
info@globestock.co.uk www.globestock.co.uk @Globestock\_Ltd

PL: 4, Issue: 06. Globestock® Ltd reserve the right to change specifications without prior notice. © Globestock 2016.

ENGINEERING PROTECTION SINCE 1982