


Green Pin Super[®] Bow Shackle with Screw Collar Pin – GPSUPSC





- Grade 8 alloy steel body and pin, quenched and tempered.
- Hot dipped galvanised finish.
- Conforms to ASME B30.26 and meets the W.L.L. performance requirements of US Fed. Spec.
 RR-C-271 Type IVA Class 3, grade b.
- Minimum breaking load is 5 times the W.L.L.
- Temperature range -20°C up to +200°C.
- Full CAD support available upon request.

Certification available 2.1 3.1 DoC

Green Pin[®] Super Screw Pin Shackles are lightweight shackles which are useful for li ing jobs in which assembly and disassembly of the load occurs frequently. The grade 8 material of which the shackle is made ensures a higher WLL than a standard shackle of the same size. To reduce wear and increase the life span of counter components that rest on the pin (e.g. chain, wire and

synthetic rope), all Green Pin[®] Super Screw Pin Shackles have a chamber in the shackle eye which hides the screw thread. Like all Green Pin[®] Super Shackles, this new screw pin shackle can be recognised by the green coloured crown.

G-5261

Product Code	W.L.L.	А	В	С	D	E	F	G	н		J	Weight	Technical
	t	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kgs	Specification
GPSUPSC3.3	3.3	13	16	34	13	22	51	32	89	73	58	0.36	Download
GPSUPSC5	5	16	19	40	16	27	64	43	110	89	75	0.63	Download
GPSUPSC7	7	19	22	46	19	31	76	51	129	103	89	1.01	Download
GPSUPSC9.5	9.5	22	25	52	22	36	83	58	144	119	102	1.5	Download
GPSUPSC12.5	12.5	25	28	59	25	43	95	68	164	137	118	2.21	<u>Download</u>
GPSUPSC15	15	28	32	66	28	47	108	75	185	153	131	3.16	Download
GPSUPSC18	18	32	35	72	32	51	115	83	201	170	147	4.31	Download
GPSUPSC21	21	35	38	80	35	57	133	92	227	186	162	5.58	<u>Download</u>
GPSUPSC30	30	38	42	88	38	60	146	99	249	203	175	7.43	<u>Download</u>
GPSUPSC40	40	45	50	103	45	74	178	126	300	243	216	12.5	<u>Download</u>
GPSUPSC55	55	57	57	117	57	83	197	138	341	286	252	17.2	Download
GPSUPSC85	85	70	70	143	70	105	260	180	437	354	320	37.6	<u>Download</u>