


Green Pin® Theatre Bow Shackle with Screw Collar Pin – GPTHB







- Grade 6 high tensile steel, quenched and tempered.
- Matt black finish.
- Conforms to BS EN 13889 (from 0.5t) and meets the performance requirements of US Fed. Spec. RR-C-271 type IVA class 2, grade A.
- Minimum breaking load is 6 times the W.L.L.
- Temperature range -40°C up to +200°C.
- Full CAD support available upon request.
- Certification available 2.1 3.1 DoC

All of the performance, none of the reflections. The Green Pin Standard Bow Shackle with Screw Collar has been specially developed for use in theatres and other entertainment venues. Due to its black matt finish, the Theatre Shackle shows no sheen or light reflections and therefore does not distract from the performance on stage. The screw pin enables quick (dis)assembly which makes the shackle perfect for rigging activities in which assembly and disassembly occur relatively frequently.

P-4161T

Product Code	W.L.L.	А	В	С	D	E	F	G	н	I	J	Weight
	t	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kgs
GPTHB.33	0.33	5	6	12	5	9.5	22	16	36	29.5	26	0.02
GPTHB.5	0.5	7	8	16.5	7	12	29	20	48.5	38	34	0.05
GPTHB.75	0.75	9	10	20	9	13.5	32	22	56	46.5	40	0.1
GPTHB1	1	10	11	22.5	10	17	36.5	26	63.5	54	46	0.14
GPTHB1.5	1.5	11	13	26.5	11	19	43	29	74	59.5	51	0.19
GPTHB2	2	13.5	16	34	13	22	51	32	89	73	58	0.36
GPTHB3.25	3.25	16	19	40	16	27	64	43	110	89	75	0.63
GPTHB4.75	4.75	19	22	46	19	31	76	51	129	103	89	1.01
GPTHB6.5	6.5	22	25	52	22	36	83	58	144	119	102	1.5
GPTHB8	8.5	25	28	59	25	43	95	68	164	137	118	2.21