

Axon specialist access harness

H20

Developed for Rope Access and suitable for all other work at height. Ergonomically designed shoulder, waist and leg pads for greater comfort.

- Large central waist D-ring configuration allows multiple attachments
- Adjustable and releasable padded shoulder straps
- Integral delta screwlink for fitting a chest ascender
- Folding side D-Rings
- Elasticated webbing keepers
- 3 reinforced gear loops with PVC tube
- Front (chest) and rear fall arrest attachment points

Shoulder strap configuration ensures good fit with maximum comfort and security.

Large waist D-ring with webbing loop allows easy attachment of descenders, ascenders and cows tails. Pivots forward when not loaded to reduce bulk at front of harness.

Alloy karabiner is quick and easy to connect. Hook free gate prevents snagging and reduces potential webbing damage. Captive bar ensures correct orientation in use.

Integral delta screwlink simplifies attachment and use of chest ascenders. Screwlink can be removed if not required.

Fast, simple adjustment of all areas of harness inc. leg loops or optimal fit. Aluminium D rings throughout reduce overall weight. Side D-rings allow work positioning attachments and fold away discreetly. Adjuster buckle geometry combines easy adjustment and positive locking. Elastic keepers stow webbing tails away. Lightweight, durable gear loops with 20kg SWL. ID labels positioned to give extended life and reduced risk of snagging.

Complies with Siemens PPE requirements PRO-13838 Ap1

Size:

H20 Standard - Torso 95-120cm, Waist 70-140cm, Thigh 60-80cm

H20L Large - Torso 100-135cm, Waist 80-165cm, Thigh 60-100cm

Also available:

H20Q Standard - Quick connect leg loop

H20QL Large - Quick connect leg loop



Specifications:

Size: Standard

EN Test Mass: 140kg

Loading: Fall Arrest & Rescue Loads

Conformity: EN358, EN361, EN813

Materials: Polyamide, mild steel & aluminium

Weight (kg): 2.05

Industries: A work at height