



Model HX 150

**Scissor elevating platform,
mobile with single scissor
model HX**

**Capacity 150 - 750 kg,
platform height max. 1000 mm**

For the independant lifting and supplying of loads within a warehouse environment.

Features

- Hydraulic lifting of the load with foot pedal.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Ergonomic handlebar for easy operation, tiltable for model HX 150.
- Steering roller with brake for safe parking of the hand stacker.
- Robust construction with hard chromium plated piston and pressure relief valve.

Technical data model HX

Model	HX 150	HX 300	HX 500	HX 750
Art.-No.	034600020	040057357	040057358	040057360
Capacity, kg	150	300	500	750
Platform height max. $h_3 + h_{13}$, mm	720	880	880	1000
Platform height min. h_{13} , mm	220	285	285	420
Stroke h_3 , mm	500	595	595	580
Lifting height per pump stroke, mm	27	31	31	15
Overall height h_1 , mm	960	984	984	990
Overall length L_1 , mm	908	1093	1093	1330
Overall width b_1 , mm	450	500	500	600
Platform length P_1 , mm	700	850	850	1000
Platform width P_2 , mm	450	500	500	510
Tyre type ¹	PUR/PUR	PUR/PUR	PUR/PUR	PUR/PUR
Rollers, mm	100x36	128x40	128x40	147x50
Number of wheels/load rollers	2/2	2/2	2/2	2/2
Weight, kg	49	78	82	120

¹ PUR... Polyurethane

