

# TECHNICAL DATA SHEET

## FIXED I-BEAM ANCHOR

TDS142



### Checkmate Fixed I-beam Anchor

Checkmate fixed I-beam anchor connects to a wide range of H & I beam flanges from 125-300mm wide and up to 30mm thick. The I-beam anchor can be installed for both horizontal and vertical use and once attached provides a secure anchor point for safe working at height.

The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information.



#### Lock-release Screws

Two knurled lock-release screws for easy and safe installation.



#### Clamp Jaws

The steel alloy clamp jaws can be secured to fit I & H beams ranging from 125-300mm wide, up to 30mm flange thickness.



#### Vertical & Horizontal Use

The beam anchor can be installed for both horizontal & vertical use. In horizontal use can be fitted to top or bottom flange.



#### Connection Point

Swivelling and rotating connection point aligns to the load direction to prevent twisting.

### specifications

- ▶ 15kN MBL
- ▶ Flange width 125mm-300mm

### principal materials

- ▶ Aluminium & steel alloy
- ▶ Anodised finish

### standards

- ▶ EN 795:1996

### ordering information

Part No.	Description	Weight
▶ YAA003	Fixed I-Beam Anchor	4.7kg



CHECKUSOUT

[www.checkmateuk.com](http://www.checkmateuk.com)

