

## Tool lanyard, 1.3m elasticated 4kg WLL

MTTE130

### Elasticated tether for attaching hand tools

Dropped objects are a major hazard. The ToolTec range of tool tethers and bolt bags allows you to control this risk more effectively.

Snaphook and screwlink end connectors available.

Elasticated design shortens the lanyard when not under load to reduce risk of tangling. Retracts by around 50% when not under load.

Elastic strength is optimised to reduce user fatigue. Requires a force of under 1kg to extend to full length.

Range of lengths available:

1.3m (MTTE130)

1.7m (MTTE170)

2m (MTTE200)

Longer lengths are used to tether tools to MEWPS etc.

4kg WLL

Tool attachments are available to work with heightec tool tethers.

To take in to account the impact force of the dropped object, tool tethers are rated for maximum length of tether and mass of tool combined.

MTTA02 - Adjustable choking loop - cord

Should be choked on to tool then secured with the toggle, preferably through a captive eye.

WLL 0.5kg x 1.95m max

MTTA03 - Non-adjustable choking loop - webbing

May be choked onto tool or harness belt webbing to form an attachment point.

WLL 4kg x 2.4m max



### Specifications:

Size: 59cm retracted, 124cm fully stretched

EN Test Mass:

Loading: 4kg WLL

Conformity: N/A

Materials:

Weight (kg):

Industries: