

Specification Sheet: Minifor™ SY with wired control pendant

Operated by a control pendant (2.5 m cable, Up/Down/Emergency Stop), which is supplied as standard. Power supply cable length 1 metre, with CEE Form connector.

Model	Product Code	WLL (kg)	Lifting Speed (m/min)	Volts (V)	Frequency (Hz)	Amp (A)	Duty Cycle	Weight (kg)
TR125 SY	243999	125	15	110	60	9	20%	21
TR125 SY	245159	125	15	110	50	9	20%	21
TR125 SY	245169	125	30	230	50	6.2	30%	20
TR125 SY	245179	125	15	230	50	3.9	30%	20
TR125 SY	245189	125	30	400	50	2.25	100%	20

Specification Sheet: Minifor™ SY for Plug-in control pendant

The control cable length can be flexibly adapted by using the version with connector. The system must be assembled with a removable plug-in control pendant (to be ordered separately) and an optional extension cable.

Model	Product Code	WLL (kg)	Lifting Speed (m/min)	Volts (V)	Frequency (Hz)	Amp (A)	Duty Cycle	Weight (kg)
TR125 SY	245259	125	30	690	50	1.3	100%	22
TR125 SY	245249	125	30	400	50	2.25	100%	20
TR125 SY	245239	125	15	230	50	3.9	30%	20
TR125 SY	245229	125	30	230	50	6.2	30%	20
TR125 SY	245219	125	15	115	50	9	20%	21
TR125 SY	245209	125	15	115	60	9	20%	21

Specification Sheet: Minifor™ SY with radio remote control

The minifor™ is equipped with radio control (integrated).
Standard range: 70 metres

Model	Product Code	WLL (kg)	Lifting Speed (m/min)	Volts (V)	Amp (A)	Duty Cycle	Weight (kg)
TR125 SY	245299	125	30	400	2.25	100%	20
TR125 SY	245289	125	30	230	6.2	30%	20
TR125 SY	245279	125	15	230	3.9	30%	20
TR125 SY	245269	125	15	115	9	20%	21