



FIRE HOSE REELS

BRITISH STANDARD BS EN 671-1 APPROVED

KEY USERS

- Major Industrials
- Marine & Off-Shore
- Petrochemicals
- Oil & Gas
- Aviation
- Nuclear
- Waste Recycling
- Civil Defence
- Construction

KEY FACTS

- Manufactured to BS EN 671-1
- Fixed & Swinging Options
- Manual & Automatic Models
- 19mm & 25mm Tube Options
- Available as 'Drum Only' or supplied (loose) with Hose Reel Tubing
- Salt Spray Resistance Tested
- Polyester Powder Coated
- Quick, Easy Installation



**19mm & 25mm
Hose Reel Tubing**

Doc Ref: DDS064

GENERAL DESCRIPTION

Delta **Hose Reels** are manufactured and approved to British & European Standard BS EN 671-1 and comply fully to the stringent tests required guaranteeing excellent durability and performance.

The Hose Reel side plates are protected with a polyester powder-coating that complies with the Salt Spray Test requirements as specified in ISO 9227 requiring exposure to salt spray for 240 hours.

Delta Hose Reels have been designed to provide a flow rate of 27 LPM (7 USG) for the 19mm (3/4") and 35 LPM (9 USG) for the 25mm (1") models. Maximum working pressure 12 bar.

Delta provide a wide range of Hose Reels including Manual, Automatic, Swinging & Fixed options in both 19mm & 25mm models. The Automatic models have an integral valve built into the hose reel unit that opens fully after three revolutions of hose has been pulled out releasing the water stream. Once recoiled the valve shuts off automatically.

The Delta Hose Reels are supplied with a quick installation mounting bracket allowing one-man fitting.

THE RANGE

Automatic	Swinging Product Code	Fixed Product Code	Drum Capacity	Side Plate Diameter	Maximum Working Pressure
	FHR120030	FHR110030	30m x ¾"	558mm (22")	12 bar
	FHR140030	FHR130030	30m x 1"	558mm (22")	12 bar
Manual					
	FHR115030	FHR105030	30m x ¾"	558mm (22")	12 bar
	FHR135030	FHR125030	30m x 1"	558mm (22")	12 bar

Dimensions (Fixed)


Drum projection (drum only) - 260mm
 Drum (drum + wall bracket) - 185mm

Dimensions (Swinging)

Drum projection + wall bracket (swung out) - 525mm
 Drum projection + wall bracket (swung in) - 280mm



Delta's **Prima Foam Units** are ideal for use with Delta Hose Reels and are easily connected to either 19mm or 25mm models. The Prima is capable of producing the equivalent fire power of 40 x standard foam extinguishers. A choice of either Low or Medium Expansion foam Prima Units are available. For more information see our Prima data sheet.



DELTA FIRE

Broadland Business Park, Norwich, Norfolk, UK, NR7 0FE

T: +44(0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk

deltafire.co.uk