



ROV Anchor Shackle with Fishtail handle and safety pin

- Yoke ROV shackles with the addition of shackle pins with a fishtail interface.
- The ROV shackle range can be offered from 6.5t to 35t.
- Working Load Limit clearly embossed on every shackle.
- Shackles painted yellow for superior visibility and shackle pins are galvanised.
- Minimum Ultimate Load is 5 times the Working Load Limit.
- Maximum Proof Load is 2 times the Working Load Limit.



SPECIFICATIONS

Part Code	Size mm	WLL tonnes	Breaking Force tonnes	A mm	B mm	C mm	D mm	E mm	G mm	H mm	I mm	J mm	Mass Kg
8-941-22	22	6.5	32.5	22	26	53	21.5	38	58	148	420	102	1.5
8-941-26	26	8.5	42.5	26	28	61	23	44	68	166	429	120	2.7
8-941-28	28	9.5	47.5	28	32	68	27	46	74	190	454	130	3.2
8-941-32	32	12.0	60.0	32	36	76	29.5	54	84	210	467	148	4.3
8-941-36	36	13.5	67.5	36	38	84	32	59	92	232	477	164	5.4
8-941-38	38	17.0	85.0	38	45	92	35	60.5	97	254	489	175	7.4
8-941-45	45	25.0	125.0	45	50	106	44	73	127	313	536	221	12.8
8-941-50	50	35.0	175.0	50	57	122	50.8	83.5	146	347.5	560	247.7	18.2

Part Code	Size inches	WLL lbs	Breaking Force tonnes	A in	B in	C in	D in	E in	G in	H in	I in	J in	Mass lbs.
8-941-22	7/8	14,330	32.5	0.9	1.0	2.1	0.8	1.5	2.3	5.8	16.5	4.0	3.3
8-941-26	1	18,739	42.5	1.0	1.1	2.4	0.9	1.7	2.7	6.5	16.9	4.7	5.9
8-941-28	1 - 1/8	20,943	47.5	1.1	1.3	2.7	1.1	1.8	2.9	7.5	17.9	5.1	7.0
8-941-32	1 - 1/4	26,455	60.0	1.3	1.4	3.0	1.2	2.1	3.3	8.3	18.4	5.8	9.5
8-941-36	1 - 7/16	29,762	67.5	1.4	1.5	3.3	1.3	2.3	3.6	9.1	18.8	6.5	11.9
8-941-38	1 - 1/2	37,478	85.0	1.5	1.8	3.6	1.4	2.4	3.8	10.0	19.3	6.9	16.3
8-941-45	1 - 3/4	55,115	125.0	1.8	2.0	4.2	1.7	2.9	5.0	12.3	21.1	8.7	28.2
8-941-50	2	77,161	175.0	2.0	2.2	4.8	2.0	3.3	5.7	13.7	22.0	9.8	40.0

The Mount
 566 Eutruria Road
 Newcastle under Lyme
 ST5 0SU