

Midas[®] SENSOR CARTRIDGE SPECIFICATIONS

Carbon Monoxide (CO) MIDAS-S-COX, MIDAS-E-COX



Gas Measured	Carbon Monoxide (CO)
Cartridge Part Number	MIDAS-S-COX 1 year standard warranty MIDAS-E-COX 2 year extended warranty
Sensor Technology	3 electrode electrochemical cell
Measuring Range (ppm)	CO 0 – 100ppm
Minimum Alarm 1 Set Point	12.5ppm
Repeatability	< ± 2% of measured value
Linearity	< ± 2% of measured value
Response Time $t_{92.5}$	≤ 60 seconds
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions
Operating Temperature	0°C to +40°C (32°F to 104°F)
Effect of Temperature	
Zero	< ± 0.035ppm / °C
Sensitivity	< ± 0.8% of measured value / °C
Operating Humidity (continuous)	15 – 90% rH
Effect of Humidity	
Zero	< ± 0.02ppm of measured value / % rH
Sensitivity	No effect
Operating Pressure	70 – 110kPa
Effect of Position	No effect in typical application
Long Term Drift	
Zero	< 2ppm / year
Sensitivity	< ± 5% of measured value / year
Calibration Gas	Carbon Monoxide (CO)
Challenge Gas (Bump Test)	Carbon Monoxide (CO)
Warm Up Time	< 10 minutes
Storage Temperature	+5°C to +25°C (+41°F to +77°F)

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

Cross Sensitivities

Each Midas[®] sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration Applied (ppm)	Reading (ppm CO)
Acetone	(CH ₃) ₂ CO	1000	0
Acetylene	C ₂ H ₂	40	80
Ammonia	NH ₃	100	0
Carbon Monoxide	CO	100	100
Chlorine	Cl ₂	2	0
Ethanol	C ₂ H ₅ OH	2000	3
Ethylene	C ₂ H ₄	100	110
Hydrogen	H ₂	100	35
Hydrogen Sulphide	H ₂ S	25	0
Iso Propanol	C ₃ H ₇ OH	200	0
Nitric Oxide	NO	50	8
Nitrogen Dioxide	NO ₂	800	20
Sulphur Dioxide	SO ₂	50	0.5

Find out more

www.honeywellanalytics.com

Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.