

# TECHNICAL DATA SHEET

## ROUNDSLING

TDS138



Roundsling Technical Data Sheet

### Checkmate Roundslings

Standard and heavy duty roundslings are made from high tenacity polyester yarn encased in a colour coded tubular sleeve of durable woven polyester fabric.



### product features

- ▶ Standard SWL: 1,000kg up to 12,000kg- colour coded
- ▶ Heavy duty SWL: 12t up to 150t
- ▶ Circ: Up to 40m
- ▶ Factor of safety: 7:1
- ▶ High strength to weight ratio
- ▶ Absorbs shock loads
- ▶ Light and flexible makes them easy to handle
- ▶ Wear sleeves available to protect from abrasion and sharp objects in either webbing or polyurethane
- ▶ Helps prevent damage to the surface of goods being lifted
- ▶ Unaffected by grease, oil, dirt, sunlight, humidity or sea water
- ▶ Certificates of conformity are supplied with goods
- ▶ Easily examined

### principal materials

- ▶ Polyester

### standards

- ▶ EN 1492-2:2000

### ordering information

Part No.	Description	Weight
▶ RS# *	Various lengths and tonnage roundslings	N/A

# = Circ e.g. 5M = 5 metre circumference

\* = Tonnage e.g. 5T = 5 tonnes

e.g. RS55 = 5 metre 5 tonne roundsling



CHECKUSOUT

[www.checkmateuk.com](http://www.checkmateuk.com)



The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information.

TDS138

ISSUE 03