

TECHNICAL DATA SHEET

TWIN LEG RESTRAINT LANYARD

TDS172



CHECKMATE Restraint Webbing Lanyards

Fixed length single or twin leg restraint webbing lanyards with a selection of connectors offer a variety of uses where the user needs to work without the risk of a fall.

Note - Lanyard length is measured between the bearing points of the hooks. Exchanging a karabiner for a scaffold hook could lengthen a lanyard beyond the maximum allowable length under the relevant EN standard.



25mm Polyester Webbing
Strong and durable with contrast stitching to aid visual inspection.



Twin Leg
Twin leg lanyards allow for 100% safe tie off when moving between anchorages.



Protected Label
Label is shrink wrapped to protect the print from daily wear and tear.



Connector Options
A- Alloy Snap Hook
B- Alloy Twist Lock Karabiner
C- Alloy Scaffold Snap Hook
D- Alloy Twist Lock Scaff Hook
E- No Fittings



Sliding Alloy Adjuster
A simple sliding adjuster enables the user to adjust the lanyard length to suit the work task.

ordering information

Part No.	Description	Weight
▼ LRT-#+++	Twin Leg Restraint Lanyard	0.6kg (LRT-2BBB)
▼ LRTA-#+++	Adjustable Twin Leg Restraint Lanyard	0.7kg (LRTA-2BBB)

Denotes length in metres
 + Denotes end fittings (A,B,C,D)
 Endless variant also available upon request

Available Lengths
 LRT: 0.5- 2m
 LRTA: 0.75-4m



A=	End Fitting
PART CODE	PPEH-45
DESCRIPTION	Alloy snap hook
GATE OPENING	20mm
STANDARDS	EN362 & ANSI



B=	End Fitting
PART CODE	PPEH-76
DESCRIPTION	Alloy twist lock karabiner
GATE OPENING	22mm
STANDARDS	EN362 & ANSI



C=	End Fitting
PART CODE	PPEH-47
DESCRIPTION	Alloy scaffold hook
GATE OPENING	63.5mm
STANDARDS	EN362 & ANSI



D=	End Fitting
PART CODE	PPEH-09
DESCRIPTION	Steel twist lock hook
GATE OPENING	51mm
STANDARDS	EN362

product features

- ▼ **Webbing strength**
22kN - minimum breaking load
- ▼ **Maximum Length**
LRT - 2 metres
LRTA - 4 metres
- ▼ **User Weight**
100Kg Maximum

principal materials

- ▼ **Webbing**
25mm Polyester
- ▼ **End Fittings**
Alloy or Steel
- ▼ **Adjustable Slider**
Aluminium

standards

- ▼ EN 354 & EN 358
(excluding restraint lanyards longer than 2m, which do not claim conformance to EN 354)



CHECKUSOUT

www.checkmateuk.com

