


Applications

Cable drum lifting.



Description

These accessories are adapted to many cable drums*. They fit holes with diameters from 55 to 83 mm. Shackles and slings not provided.

* ABN/ BBN/ CBN/ DBN/ EBN/ FBN/ GBN/ HBN/ IBN type following NF B 55-007 French standard.

Functioning

Once both shackles and 2-legged cable/ chain/ textile slings have been put together with the hooks, insert them either side of the cable drum axle, teeth downwards. Lifting ensures the hooks' locking in position.

Important instructions

- The hooks and cable drums' bearing surface must be free from grease or oil.
- Insert hooks in the right direction, ie. teeth downwards.
- Working temperature: -20° to +100°C.

General characteristics

- Manufactured without load bearing welds.
- Hot epoxy coating.
- Safety factor: 3 in accordance with the EN 13155.2003 nom.
- Product conforms to the French regulation, in particular the decree of 01/03/2004 relating to the check on lifting devices and the European Directive n°2006/42/CE.
- Product with EC marking and delivered with a declaration of conformity and instructions for use.

Dimensional characteristics

Ref.	Group code	WLL/ pair kg	A	B	D	E	L	Weight/ pair kg
TO13	51198	13 000	265	112	27	35	180	6

Dimensions in mm

