



EUROSTYLE®



Range of jib cranes mounted on a wall or on a column, with total or partial rotation capability, manual or motorized.

 **VERLINDE**
LIFTING EQUIPMENT



EUROSTYLE

Individual handling is essential to each workstation to prevent a slowdown in the production rhythm when using the traveling crane in service at the production plant.

VERLINDE offers a wide range of jib cranes that are strong, with a nice design, high performance and equipped with the following range of hoists: EUROCHAIN VR, EUROBLOC VT, EUROLIFT BH, or EQUIBLOC AIR :

- > **Designed in compliance with DIN 15018 standards, all steel.**
- > **2m group classification.**
- > **The arm is made with IPE shaped steel beam resistant to torsion constraints (fitted with 2 adjustable stops for VFP & VFM), or with EUROSISTEM-type hollow shaped steel beam (VATS & VTFS).**
- > **Temperature rating -10° C to +40° C.**
- > **IP 44 (IP 55 available upon request) protection rating of power supply lines, cutout, etc.**
- > **Finish: shot-blast frame, primer and yellow finish glossy paint RAL 1028.**



VATAL

Loads of 63 to 2,000 kg.
Span from 2 to 8 meters
according load.

Description

- > Light construction.
- > EUROSISTEM ALU hollow-section, aluminum wall jib crane for indoor use, 180° rotation, with overbraced beam.
- > This type of jib crane cannot be motorized.
- > Horizontal and vertical reactions are understood to be under nominal load.
- > RAL 1028 yellow polyurethane finish for the attachment.
- > Attached with M24, 10.9 grade bolts (not provided).

- > Hoist trolley provide.
- > Power supply cable provided.
- > Maximum hoisting speed = 16 m/min.

Options

- > Lockable main switch.
- > Rotation slowing device (adaptable without welding or mechanical intervention).
- > Rotation stops to bolt.
- > Single or multi-position rotation lock.
- > Electric or manual hoist.



VAI

Loads of 125 to 4,000 kg.
Span from 2 to 7 meters
according load.



Options

- > Hoist power supply cable + lockable main switch.
- > Standpipe.
- > Rotation slowing device (adaptable without welding or mechanical intervention).
- > Hot dip galvanizing (contact us).
- > Rotation stops to weld onto the assembly.
- > Single or multi-position rotation lock.
- > Outdoor use.
- > Motorization.
- > Electric or manual hoist.

Description

- > Wall jib crane for indoor use, 180° rotation, with underbraced beam.
- > Uses M24, 10.9 grade bolts (not provided) for attachments N°1 and N°2, and M27, 10.9 grade bolts (not provided) for attachments N°5 and N°6.
- > Protection: 3-layer system.
- > RAL 1028 yellow polyurethane finish.
- > Maximum hoisting speed = 16m/min.

