# RGEABLE HEADTORCH



HT-500 ZONES 1 2 21 22









## PRODUCT INFORMATION

Available from Wolf, the HT-500 Petzl Duo Z1 is a powerful, Zone 1 Rechargeable multi-beam Headtorch for use in Hazardous Areas, featuring four lighting modes and a maximum output of 360 lumens on BOOST mode.

Four lighting modes including FACE2FACE anti-glare function



## **KEY INFORMATION**

PRODUCT CODE	ZONE GAS/DUST	LIGHT OUTPUT (LUMENS)	BATTERY DURATION	POWER SOURCE
HT-500	1/21	360	Up to 23 hours	Rechargeable

### LIGHT OUTPUT/DURATION/POWER

- Long life LED light source
- Multiple beam options for varying work tasks: BOOST mode 360lm, distance vision 140lm, movement 300lm, proximity 170lm & close range work 70lm
- Duration at different power levels: 7, 12, 17 & 23 hrs.
- Additional 'reserve mode' provides 10lm for 1.5 hrs
- Rechargeable Lithium-Ion battery charges in 8 hrs.
- Flood, spot and mixed beam options, depending on power setting

### **CERTIFICATION**

- ATEX Zone 1/21
- T4 temperature class
- IP67 water and dust tight

## **FEATURES**

- FACE2FACE anti-glare feature, allows users to face one another without blinding
- Robust, reliable and proven materials
- Ergonomic design
- · Compact and lightweight
- Large tactile switch (easy to use even when wearing gloves)
- · Highly robust
- Helmet ready with mounting plates included for VERTEX and STRATO helmets

VERSION: SL103 DF-572 ISSUE 2 WWW.WOLFSAFETY.COM

## **TECHNICAL INFORMATION**

ATEX RECHARGEABLE HEADTORCH				
PRODUCT REFERENCE		HT-500		
PRODUCT DESCRIPTION		ATEX Rechargeable Headtorch		
CODE		II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db		
TYPE OF PROTECTION		ʻib' intrinsic safety		
AREA OF CLASSIFICATION (GAS)		Zones 1		
TEMPERATURE CLASS (GAS)		T4		
AREA OF CLASSIFICATION (DUST)		Zone 21		
MAX. SURFACE TEMP. (DUST)		T135° C		
AMBIENT TEMPERATURE		-20° C to +40° C		
CERTIFICATE		LCIE17ATEX3009X		
ВЕАМ ТҮРЕ		Flood, Spot or Mixed		
LIGHT SOURCE	ТҮРЕ	High Power LED		
	OUTPUT	Up to 360 lumens		
POWER SOURCE	PART NO.	HT-500/ACCU2		
	ТҮРЕ	Lithium-lon ACCU 2 DUO Z1 battery		
	VOLTS	3.7 V		
RECHARGE TIME		8 hrs		
LIGHT DURATION		Up to 23 hrs (Reserve mode 10lm for 1.5hrs)		
INGRESS PROTECTION		IP67		
WEIGHT (INC. CELLS)		370g		

All information has been gathered under laboratory conditions, the user must regard the values given as approximate. Changes may be made to the above specification without notification, details are available on request.

## **ACCESSORIES**

For full accessories information, please visit: https://www.wolfsafety.com/accessories/ht-500-rechargeable-headtorch-accessories

#### HT-500/ACCU2

Rechargeable Battery for the HT-500, useable in ATEX environments.



### HT-500/ADPT

Adhesive accessory for mounting a HT-500 on any type of helmet.



# PACK OF 5 HT-500/5 - HEADTORCHES WITH CHARGING RACK

Pack of 5 HT-500s with charging rack.





Wolf Safety Lamp Company Saxon Road Works, Sheffield S8 0YA, UK

T: +44 (0) 114 255 1051 **E: info@wolfsafety.com** 





VERSION: SL103 DF-572 ISSUE 2 WWW.WOLFSAFETY.COM